

Installation Instructions Programming #75424 Marantec Plug-In Radio Receiver

Although Marantec supplies installation instructions with the #75424 Plug-In Radio Receiver we have found them to be a little confusing so we are supplying these supplemental instructions. We hope they clear up any confusion you may have.

1. Remove the Plug-in Unit, control wiring and remote from the packaging.
2. Connect the 2-conductor wire to the Plug-in Unit. The two wires push in to the base of the unit.
3. Connect the other end of the 2-conductor wire to the garage door power head (see the top picture on the back of the instructions supplied by Marantec). Insert the **white single wire** into **terminal #3** and the **single colored** (actually it has gray dashes) into **terminal #4**.
4. Plug the unit into an electrical outlet.
5. **PROGRAMMING** - Press & release the oval program button on the #75424 Plug-In Radio Receiver (located on the bottom front of the plug-in receiver)

Press the button on the remote control, the LED (program button) should light up for approx. 4 seconds. Once the light on the program button goes out the garage door opener can now be operated by the new remote. Congratulations - you now have a working garage door opener.

-
6. **Multiple Remotes:** This final instruction is only needed if you have more than one remote:
 - A. If you have another M3-2312 (or M3-3313 or M3-2314) Remote then you'll need to use the jumper that was included with the remote. Plug the remote that you programmed above into the second remote. Press and hold the programmed remote button. While holding the button down, press and hold the button on the second remote. The LED lights on the remote should flicker. Now both remotes are programmed to the Plug-in unit.

